

# GS-IP-5053-MQ-33X

## Features

- Support human detection and AI human tracking
- Support ONVIF protocol and access to third-party platform
- H.265+/H.265/H.264
- 6KV lightning strike protection
- IP66 Rating
- Support P2P function
- Support a variety of cloud technologies, alarm information pushed to cell phones and other functions
- Support Web side, CMS, MYEYE and SDK development



## Specification:

Model No.	BT-HD608-AI-SL
<b>Camera</b>	
Solution:	GK7205V300+1/2.8" SC5239P CMOS
Image	5MP 2880*1616@25fps 33X OPTICAL ZOOM
Solution	GK7205V300+1/2.8" IMX335 CMOS
Image	5MP 2880*1616@25fps 33X OPTICAL ZOOM
Digital Noise Reduction	2D/3D DNR
Image setting	Auto white balance; Auto exposure; Backlight compensation; Support D-WDR; Electronic defogging; Daylight anti-flash
General Function:	Horizontal flip and vertical flip
Lightning Protection	Comprehensive lightning protection of power supply and network
Business Function	Support: WEB configuration, OSD, motion detection, center alert after motion detection alarm, screen pop-up linkage, MJPEG capture, VMS remote monitoring software, MYEYE platform and other system applications, SDK development kit

<b>Lens</b>	
Lens Type	6±5%~108±5%mm
Iris Type	Wide: Diagonal 62.0° Horizontal: 54.8° Vertical: 31.5° Tele: Diagonal 4.1° Horizontal: 3.59° Vertical: 2.03°
Aperture	F1.8~F3.9

Rotation Control	
Range	Pan: 360° Pan: 0-93°
Speed	Pan: 45°/s Tilt:30°/s

Video	
Video Compression	Support H.265+/H.265/H.264; Support dual stream and AVI format; Code stream 0.1M~8Mbps adjustable; Frame rate 1~30 fps adjustable

Audio	
Audio Compression	G.711

AI+	
General SC5239P	Support human detection, and intelligent function customization
General IMX335	Support human detection, and intelligent function customization
Alarm	APP alarm, sound alarm

Network	
Protocols	Support RTSP/ FTP/ DHCP/ NTP/ UPNP/ Onvif/ protocol, etc.

APP	
Mobile View	Android, IOS

Interface	
Communication Interface	1 RJ45 10 M / 100 M Ethernet interface
General IMX335	Built in
Speaker	Built in
Reset	Not Support

Light	
IR Distance	Up to 200m
LEDS	+6PCS IR LED

Rotation Function	
Preset Point	220 pcs
A-B Scan/Guard	Support
Auto Tracking Range	3M-50M

General	
Power Supply	DC : 12V±25%
Power Connector	Ø5.5mm circular interface
Operating Conditions	-30°C ~ 55°C
Factory Data Reset	Support software to restore factory settings
Material	Metal + plastic
Weather Proof Rating	IP66